

ACA-BL10SS-100

LHD Cable Accessory - Bracket "L", 100mm (3.9") (St Steel) w/ Sleeve - Pack of 100

L-Bracket

The ACA-BL series L-brackets is designed to support linear heat cable above the risk area e.g. the top run of a cable tray. A silicon protection sleeve is supplied with the unit to protect the sensor cable when fastened to the bracket.

Installation

The ACA-BL may be fitted to the cable tray and secured in place using a suitable bolt and nut at one end. The hole at the other end of the bracket allows for the securing of the sensor cable using a silicone sleeve and cable tie. The L-bracket allows support for the sensor cable at the selected distance away from the detection area.

Recommended spacing: 1m



Details

- · Easy installation of linear heat cable
- For use on cable trays
- Available in stainless steel
- Available in quantities of 100

$ACA-BL10SS-100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Pack \ of 100\\ LHD \ Cable \ Accessory - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 100mm (3.9") (St \ Steel) \ w/\ Sleeve - \ Bracket "L", 10$

Technical specifications

20 x 100 mm (W x L)
1.65 kg
Surface mount
Stainless steel
Indoor, Outdoor

