

1-B6782-170

Retractable Cable, Coiled, Length 30m

General

Retractable cables are designed to provide electrical connection for parts that are in motion after connection e.g. a tank roof top of floating roof tanks. They reduce the risk present in normal cables of being caught and snapped during the rising and falling movement of the tank roof.

Accessories

For ease of installation, retracable cables may be used with an optional retractable cable collector, the 1-B6782-032.



Details


- Symplifies electrical connections of floating roof tanks
- Reduces cable damage in moving installations

1-B6782-170

Retractable Cable, Coiled, Length 30m

Technical specifications

No. of cable cores	4	_
- Cable cores	7	—
Conductor		
Core colours	blue, brown, black, yellow	
Diameter	1.75 mm	
Insulation	PVC	
Sheath	Polyurethane	
Physical		
Physical dimensions	0.75 mm²	
Colour	Black	
Environmental		
Operating temperature	-40 to +80°C	
Environment	Indoor, Outdoor	
Cable		
Diameter	10 mm (± 0.25)	
Sheath	Hytrel™ (Dupont)	
Tails D/E*	1.5 m (± 50)	
	5.5m (± 100)	
Working length (incl.	30 m	
tails)		
Coil		
Outer diameter (nom.)	250 mm	
A*		_
Closed length B*	580 mm (± 50)	_
Manufacturing star	ndards	
Cores	ISO 6722 Thin Wall	_





(See image below)

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.