

Slave Overdoor Light

Part No. **QT606**



Overview

- Provides visual indication of calls made from a Quantec call point outside bedrooms, WCs, etc.
- Flash and colour sequence changes/intensifies to reflect the urgency of the incoming call.
- Dual red and green LEDs and triangular diffuser make it highly visible from a distance.
- Mounts on a standard UK 25mm single gang flush or surface back box.
- Finished in tough, durable ABS plastic.



More Information

Technical Specifications

Quiescent current	0mA (none).
Alarm current	40mA.
Indicators	Dual ultra-bright red and green Alarm LEDs (Flash rate and colour sequence changes/intensifies to reflect the urgency of the incoming call).
Connections	R (Red); G (Green); Net +; Net -. Wire as a slave to a Quantec Addressable Call Point or Accessible Toilet Reset Point. See instructions for details.
Onboard Sounder	No,
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 68 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.



Weight 48g.

Operating conditions/temperature -5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom